

YANTON®

4G/LTE POC Walkie Talkie

T-X9



- Support 4G/LTE/3G/2G M network
- Support Group Call, Single Call, Friendly Call, Emergency Call
- 1.77 inch color screen
- Strobe Light Function
- RTOS System
- Bluetooth Function (Optional)
- GPS Function (optional)
- IP67 waterproof (optional)

Strobe light function



YANTON®

4G/LTE POC Walkie Talkie

T-X9



SPECIFICATION

General	Dimensions (H*W*D)	115mm*55mm*33mm(without Antenna and Belt clip)
	Weight(includes battery)	≈275G
	Working temperature	-30℃~+75℃
	Operating Voltage	DC3.3V-4.2V(Recommended value 3.8V)
	Working current	Peak current ≈0.6A
	Average current	≈540mA@UMTS2100;≈239mA@GSM900
	Stand-by current	≈5mA@UMTS;≈5mA@GSM
	Battery Capacity	3000Mah
	Charger mode	Type-c
Baseband	(U) SIM/SIMU	Standard SIM Card Slot: Support 3VSIM Card and 1.8VSIM Card
	UART Connector	8 pins UART
	Maximum power consumption	≈ 2.2uw
Frequency	UMTS Frequency Band	HSDPA/WCDMA: B1/2/3/4/5/7/8/12/13/17/34/38/39/40/41 B1/2/3/4/5/7/8/12/13/17/34/38/39/40/41
	TX Power	UMTS2100/1900/900/850:power level 3(+24dBm+2.5/-1.5dBm) EDGE850MHz/900MHz:power level E2(+27dBm+4.5/-1.5dBm) EDGE1800MHz/1900MHz:power level E2(+26dBm+4.5/-2.5dBm)
	RX Sensitivity	WCDMA2100:≤-108dBm
		WCDMA1900:≤-109dBm
		WCDMA900:≤-109dBm WCDMA850:≤-109dBm GSM850/900/1800/1900:≤-107dBm

QUANZHOU YANTON ELECTRONICS CO.,LTD. www.yantonradio.com